

# PRODUCT DATA SHEET

## Sika® Separol® FP-15 BH

OIL BASED, ANTI-CORROSIVE SHUTTER RELEASE AGENT

### DESCRIPTION

Sika® Separol® FP-15 BH is an oil based shutter / mould release agent that when applied to formwork provides for clean, fast and easy striking. Suitable for use in hot and tropical climatic conditions.

### USES

- Steel shuttering
- Plywood shutters
- High density plastic shutters

### CHARACTERISTICS / ADVANTAGES

- Allows clean, easy striking
- Extends the life of formwork
- Improved finish for fair faced concrete
- Reduces concrete contamination
- Economical to use
- Reduces blow hole formation

### PRODUCT INFORMATION

<b>Composition</b>	Blend of oil based products
<b>Packaging</b>	20 L and 200 L drums
<b>Appearance / Colour</b>	Light yellowish brown liquid
<b>Shelf life</b>	24 months from date of production if stored properly
<b>Storage conditions</b>	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5 °C and +45 °C. Protect from direct heat and sunlight.
<b>Density</b>	~0.83 kg/l (+25 °C)

### APPLICATION INFORMATION

<b>Consumption</b>	Timber:	~25 m <sup>2</sup> /kg
	Steel or plastic:	~50 m <sup>2</sup> /kg
Coverage depends on wind, humidity and temperature.		

### APPLICATION INSTRUCTIONS

Sika® Separol® FP-15 BH is supplied ready to use. Shutter surfaces must be clean and free from moisture, dirt and laitance. Apply in one even coat by brush, roller or spray.

## IMPORTANT CONSIDERATIONS

Excess application will tend to run down on vertical surfaces and pool at the bottom.  
Remove excess material using a dry cloth or sponge.  
Over application may lead to staining of the hardened concrete.  
After application to surfaces protect them from rain for at least 2 - 3 hours.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA NORTHERN GULF

Bahrain / Qatar / Kuwait  
Tel: +973 177 38188  
sika.gulf@bh.sika.com  
gcc.sika.com

### SIKA SOUTHERN GULF

UAE / Oman / SIC  
Tel: +971 4 439 8200  
info@ae.sika.com  
gcc.sika.com

### SIKA SAUDI ARABIA

Riyadh / Jeddah / Damman  
Tel: +966 11 217 6532  
info@sa.sika.com  
gcc.sika.com



ISO 9001: Sika UAE LLC,  
Sika Gulf B.S.C. (c),  
Sika Saudi Arabia Co. Ltd,  
Sika Qatar LLC  
ISO 14001: Sika UAE LLC,  
Sika Gulf B.S.C. (c),  
Sika Saudi Arabia Co. Ltd  
OHSAS: Sika UAE LLC,  
Sika Gulf B.S.C. (c)

All products are supplied  
under a management  
system certified to conform  
to the requirements of the  
quality, environmental and  
occupational health &  
safety standards ISO 9001,  
ISO 14001 and OHSAS  
18001.

### Product Data Sheet

Sika® Separol® FP-15 BH  
April 2018, Version 01.01  
02140502100000305

SikaSeparolFP-15BH-en-AE-(04-2018)-1-1.pdf