

## PRODUCT DATA SHEET

# Sikafloor® SR

(formerly MTop SR)

Selected silica aggregates for use in conjunction with Sika® systems

### DESCRIPTION

Sikafloor® SR aggregates are used with various resin products to produce industrial floors filled coatings, slip-resistant profiles and creation of mechanical key for subsequent coatings.

Available in various gradings:

Product name:	Aggregate size:
Sikafloor® SR 1	0 - 0.3 mm
Sikafloor® SR 2	0.3 - 0.7 mm
Sikafloor® SR 3	0.3 - 0.9 mm
Sikafloor® SR 5	1 - 2 mm

### USES

Sikafloor® SR aggregates when used as part of Sika® system build-ups, can be used in locations such as:

- Car Park Decks
- Kitchens
- Engineering Workshops
- Garages
- Warehouses
- Power Stations
- Agricultural Buildings
- Aircraft Hangars
- Abattoirs
- Loading Bays
- Factories

### FEATURES

- Economical
- High impact resistant
- Wear resistant
- Non-oxidising
- Improves slip resistance of flooring systems
- Improves bond
- Reduces dusting

### PRODUCT INFORMATION

Packaging	25 kg triple ply sacks
Shelf life	24 months from date of production
Storage conditions	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5°C and +35°C. Protect from direct sunlight, heat and moisture.

# APPLICATION INFORMATION

## Consumption

Refer to applicable Sika® product or system Method Statement.

## BASIS OF PRODUCT DATA

- All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
- Internal Reference - Version: MBS\_CC-UAE/Top\_SR\_02\_99/v2/09\_17/v3/09\_19/v4/01\_24

## FURTHER DOCUMENTATION

Part of the General Method Statement (GMS) of various Sika® products and system build-ups.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

Sikafloor® SR aggregates are designed to increase the impact and slip resistance of industrial coatings and flooring systems. They can be mixed with, or broadcasted over suitable resin. Also used to increase the bond between concrete substrates and multi-layer systems and to provide a mechanical key for overlay systems.

## CLEANING OF EQUIPMENT

Clean all tools and application equipment with water immediately after use.

When used with resins, refer to cleaning recommendations of particular product.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Gulf B.S.C. (c)

Tel: +973 177 38188

Email: info@bh.sika.com

Sika Kuwait Cons. Mat. & Paints Co WLL

Tel: +965 22 282 296

Email: sika.kuwait@kw.sika.com

Web: gcc.sika.com

### Sika UAE LLC

Sika MB Construction Chemicals LLC

Sika International Chemicals LLC

Tel: +971 4 439 8200

Email: info@ae.sika.com

Web: gcc.sika.com

### Sika Saudi Arabia Limited

Sika Construction Chemicals for

Manufacturing LLC

Riyadh / Jeddah / Dammam / Rabigh

Tel: +966 12 692 7079

Email: info@sa.sika.com

Web: gcc.sika.com

### Sika LLC - Oman

Master Builders Solutions LLC

(part of Sika)

Tel: +968 22 826 500

Email: info@om.sika.com

Web: gcc.sika.com



ISO 9001, 14001, 45001 – SGS  
- Sika UAE LLC  
- Sika International Chemicals LLC  
- Sika Gulf B.S.C. (c)  
ISO 9001, 14001 – SGS  
- Sika Saudi Arabia Limited  
ISO 9001, 14001 – TÜV  
- Sika MB Construction Chemicals LLC  
- Sika Construction Chemicals for Manufacturing LLC  
- Master Builders Solutions LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.



### Product Data Sheet

Sikafloor® SR

September 2024, Version 02.01

02081600000002014

