

## PRODUCT DATA SHEET

# Sika® Extender T

#### THICKENING AGENT FOR SIKAFLOOR® FLOORING RESINS

#### **DESCRIPTION**

Sika® Extender T is an inert, fine, white, fibrous polymer powder used as a thickening agent for Sikafloor® flooring resins.

Suitable for use in hot and tropical climatic conditions.

#### **USES**

- In combination with Sikafloor® epoxy, polyurethane and PMMA resins
- Applications on horizontal surfaces to create custom surface textures
- Applications on vertical surfaces to hold the resin in place during curing
- Crack and pore filler to seal horizontal and vertical surfaces

### **CHARACTERISTICS / ADVANTAGES**

- Allows for viscosity adjustment of Sikafloor® product applications
- Economical, easy to mix and use
- No effect on pot life or cure rate
- Low addition rate required to change resin viscosity
- Non carcinogenic
- Inert and non-reactive

#### PRODUCT INFORMATION

Packaging	1 kg container.
Appearance / Colour	White powder
Shelf life	2 years from date of production
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.

#### APPLICATION INFORMATION

Recommended Dosage	Refer to the individual Sikafloor® resin Product Data Sheet
--------------------	---

**Product Data Sheet** 

**Sika® Extender T**January 2020, Version 01.01
020816020040000002

#### APPLICATION INSTRUCTIONS

#### APPLICATION

#### General guide:

The required amount of Sika® Extender T is added to the Sikafloor® resin in accordance with the appropriate Product Data Sheet over a period of ~15 seconds until fully mixed without any visible lumps. Refer to the individual Sikafloor® resin Product Data Sheet for further informaton.

#### **IMPORTANT CONSIDERATIONS**

- Do not hand mix Sika® Extender T, mechanically mix only
- Gloss finish maybe affected at high addition rates.
- Adhesion characteristics may be affected at high addition rates.
- Sika® Extender T maybe visible in some clear resins at high addition rates.
- Protect from contact with moisture, Sika® Extender T must be kept dry.

#### **BASIS OF PRODUCT DATA**

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### **LOCAL RESTRICTIONS**

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

#### **ECOLOGY, HEALTH AND SAFETY**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

#### **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA NORTHERN GULF

Bahrain / Qatar / Kuwait Tel: +973 177 38188 sika.gulf@bh.sika.com gcc.sika.com SIKA SOUTHERN GULF

UAE / Oman / SIC Tel: +971 4 439 8200 info@ae.sika.com gcc.sika.com SIKA SAUDI ARABIA

Riyadh / Jeddah / Dammam Tel: +966 11 217 6532 info@sa.sika.com gcc.sika.com



Sika Gulf B.S.C. (c), Sika Saudi Arabia Co. Ltd, Sika Qatar LLC ISO 14001: Sika UAE LLC, Sika Gulf B.S.C. (c), Sika Saudi Arabia Co. Ltd OHSAS: Sika UAE LLC, Sika Gulf B.S.C. (c) All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS

Product Data Sheet
Sika® Extender T
January 2020, Version 01.01

020816020040000002



SikaExtenderT-en-AE-(01-2020)-1-1.pdf