

## PRODUCT DATA SHEET

# Sika® Igoflex®-609

(formerly MSeal 609)

Non-fibrated bitumen emulsion

### DESCRIPTION

Sika® Igoflex®-609 is a brown-black bitumen liquid emulsion with excellent adhesion, which dries to a tough, seamless, waterproof and protective coating for concrete structures and steel elements. Suitable for use in tropical and hot climatic conditions.

### USES

- Protection and damp-proofing of concrete, asbestos cement sheets, roofing felts, wood.
- Protection of steel work, pipes and metal.

### FEATURES

- Vapour permeable allows substrate to breathe
- Reduced chloride penetration due to hard impermeable surfaces
- Simple and easy to use
- Single component, use as supplied
- Solvent free
- Cold applied, no heating require
- Unaffected by high ambient temperature
- High resistance to aggressive soils and contaminated ground water
- Low odour, dries without generating strong vapours

### PRODUCT INFORMATION

<b>Packaging</b>	20 L and 200 L drums
<b>Appearance and colour</b>	Dark black / brown colour. Cures to a hard tack free finish.
<b>Shelf life</b>	12 months minimum from production date when stored properly in original, unopened, sealed containers.
<b>Storage conditions</b>	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5 °C and +35 °C. Protect from direct sunlight, heat and moisture.
<b>Density</b>	~1.1 kg/l (at 23 °C)
<b>Solid content by volume</b>	26 % ± 2 %

### TECHNICAL INFORMATION

<b>Chemical resistance</b>	Generally resistant to water, aqueous, groundwater salt solutions, mild detergents, acids and alkalis.
----------------------------	--

# APPLICATION INFORMATION

<b>Consumption</b>	Typically, a coverage rate of 3–5 m <sup>2</sup> / L / coat, dependent on substrate, porosity, texture and desired DFT specifications. Minimum 2 coats required. Site trials should be carried out to ascertain exact coverage.
<b>Drying time</b>	6–8 hours per coat at 25 °C

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTATION

- General Method Statement (GMS)

## IMPORTANT CONSIDERATIONS

Sika® Igoalflex®-609 may be applied to damp but not wet surfaces. Dampen brushes before and occasionally during use to avoid clogging and ease application. During hot, dry weather application may be assisted by dampening the surfaces to be treated.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

- All surfaces must be sound, even, free from dust, loose particles and any contamination.
- Sika® Igoalflex®-609 may be applied to damp but not waterlogged surfaces.
- Hot and very dry, porous concrete surfaces must be primed by diluting Sika® Igoalflex®-609 with clean water at 1:1 ratio (by weight).

### MIXING

- Sika® Igoalflex®-609 must be stirred well before use.
- Where a single drum is used for prolonged periods, occasional stirring during application is recommended.

## APPLICATION

- Apply evenly and in one direction using a stiff brush. A minimum two-coat application is recommended to avoid possible gaps in the film.
- Each coat must be allowed to dry before applying the next one at right angles to the first.

## CLEANING OF EQUIPMENT

Clean all equipment and tools with water immediately after use.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Gulf B.S.C. (c)

Tel: +973 177 38188

Email: info@bh.sika.com

Sika Kuwait Cons. Mat. & Paints Co WLL

Tel: +965 22 282 296

Email: sika.kuwait@kw.sika.com

Web: gcc.sika.com

### Sika UAE LLC

Sika MB Construction Chemicals LLC

Sika International Chemicals LLC

Tel: +971 4 439 8200

Email: info@ae.sika.com

Web: gcc.sika.com

### Sika Saudi Arabia Limited

Sika Construction Chemicals for

Manufacturing LLC

Riyadh / Jeddah / Dammam / Rabigh

Tel: +966 9200 22167

Email: info@sa.sika.com

Web: gcc.sika.com

### Sika LLC - Oman

Sika MB LLC

Tel. +968 22 826 500

Email: info@om.sika.com

Web: gcc.sika.com



ISO 9001, 14001, 45001 – SGS  
Sika MB LLC  
Sika International Chemicals LLC  
Sika Gulf B.S.C. (c)  
ISO 9001, 14001 – SGS  
Sika Saudi Arabia Limited  
ISO 9001, 14001 – TÜV  
Sika MB Construction Chemicals LLC  
Sika Construction Chemicals for Manufacturing LLC  
ISO 9001 – LMS  
Sika MB LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.



Sikalgoalflex-609-en-AE-(01-2025)-3-1.pdf

### Product Data Sheet

Sika® Igoalflex®-609

January 2025, Version 03.01

02070600000002041

