

PRODUCT DATA SHEET

SikaWall®-15 Tinted Primer AE

(formerly Senergy® Tinted Primer)

ACRYLIC BASED PRIMER

DESCRIPTION

An acrylic based primer for use with finishes of Sika Exterior Insulation and Finish System (EIFS), to help alleviate substrate read through, aids with color uniformity and finish shadowing.

USES

- SikaWall®-15 Tinted Primer AE helps alleviate shadowing and enhances performance of the SikaWall® finish coats range.
- SikaWall®-15 Tinted Primer AE should closely match the colour of the selected SikaWall® finish coats range.
- SikaWall®-15 Tinted Primer AE is also used when preparing substrates such as poured concrete, unit masonry, conventional stucco (brown coat), veneer plaster or gypsum board (interior only) prior to application of SikaWall® finish coats range.

FEATURES

- Reducing the absorbance of cement base coats and cementitious substrates to improve workability of finish coat application.
- Creates better final appearance, alleviates shadowing of light colored, rolled finishes.
- Reduces potential of efflorescence in stucco and other cementitious substrates.

PRODUCT INFORMATION

Composition	~100 % acrylic based primer
Packaging	24.9 kg (~19 L) unit
Colour	Available in a wide variety of standard colours
Shelf life	6 months from date of production
Storage conditions	Store in undamaged, original sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Protect from direct sunlight, heat and moisture.

APPLICATION INFORMATION

Consumption	Approximate coverage rate is 70–100 m ² per unit. Coverage will vary greatly depending on the porosity and condition of the surface.
--------------------	---

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Protect products during transportation and installation to avoid physical damage.
- Do not apply Senergy materials in ambient temperatures below 4 °C. Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C prevail.
- Do not apply to frozen surfaces.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

- Thoroughly mix the factory-prepared SikaWall®-15 Tinted Primer AE with a paddle and drill to a uniform consistency.
- A small amount of clean, potable water may be added to adjust workability.
- Additives are not permitted.
- Close the container when not in use.

APPLICATION

- Substrate shall be dry, clean, sound and free of re-leasing agents, paint or other residue or coatings.
- Verify substrate is flat, free of fins or any irregularities greater than 6.4 mm in 3 m length.
- Apply SikaWall®-15 Tinted Primer AE to substrate with a sprayer, 10 mm nap roller or good quality latex paint brush.
- SikaWall®-15 Tinted Primer AE shall be dry to the touch before proceeding to the SikaWall® finish coat range application.

CLEANING OF EQUIPMENT

Clean all tools and application equipment with clean water and soap immediately after use. Hardened / cured material can only be removed mechanically.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Gulf B.S.C. (c)

Tel: +973 177 38188

Email: info@bh.sika.com

Sika Kuwait Cons. Mat. & Paints Co WLL

Tel: +965 22 282 296

Email: sika.kuwait@kw.sika.com

Web: gcc.sika.com

Sika UAE LLC

Sika UAE LLC (Branch)

Sika International Chemicals LLC

Tel: +971 4 439 8200

Email: info@ae.sika.com

Web: gcc.sika.com

Sika Saudi Arabia Limited

Riyadh / Jeddah / Dammam / Rabigh

Tel: +966 9200 22167

Email: info@sa.sika.com

Web: gcc.sika.com

Sika MB LLC

Oman

Tel: +968 22 826 500

Email: info@om.sika.com

Web: gcc.sika.com



ISO 9001, 14001, 45001 – SGS:
- Sika UAE LLC
- Sika International Chemicals LLC
- Sika Gulf B.S.C. (c)
ISO 9001, 14001 – SGS:
- Sika Saudi Arabia Limited
ISO 9001, 14001 – TÜV:
- Sika UAE LLC (Branch)
ISO 9001 – SGS:
- Sika MB LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.



SikaWall-15TintedPrimerAE-en-AE-(03-2026)-1-1.pdf

Product Data Sheet

SikaWall®-15 Tinted Primer AE

March 2026, Version 01.01

02189020000242974

