

## PRODUCT DATA SHEET

## Sika® Stabilizer-5014 TBM SA

Plasticising admixture with set retarding properties for use in annular grout Component A for TBM application

## DESCRIPTION

Sika® Stabilizer-5014 TBM SA is a liquid plasticizer which disperses and deflocculates cement particles whilst delaying the hydration process, thereby retarding the initial and final set. It can be used to improve workability without the addition of extra water, or to allow reductions in the free water content. Due to improved dispersion of the cement particles the process of hydration of Component A proceeds under the optimum conditions, leading to improved strength characteristics with or without reduction in free water.

## USES

- High flow, low cement content, high w/c ratio annular grout mixes for TBM tunneling.
- Hot weather applications of grout where control of initial and final set is important.
- Setting control of annular grout mixes for injection behind segmental tunnel linings.

## FEATURES

- The retarding action allows storage of the annular grout in the pumping lines and grout agitator tanks on the TBM. Open time will be depending on dosage.
- Enables controlled extension of initial set of Component A.
- Highly effective in low cement content, high water cement ratio mixes, where its use enables the grout to be made more workable without loss in strength, density and durability.
- Allows a reduction in free water in the range of 5 –12 %, depending on dosage.
- The strength gain of annular grouts containing Sika® Stabilizer-5014 TBM SA is enhanced. After retardation of initial and final set, a more rapid hardening of the grout occurs, and the effect on stripping time is negligible.

## PRODUCT INFORMATION

Composition	Modified lignosulphonate
Packaging	1000 L IBC, Bulk supply in tanker trucks possible on request.
Appearance and colour	Dark Brown liquid
Shelf life	12 months from date of production if stored properly
Storage conditions	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5 °C and +45 °C. Protect from direct sunlight and frost.
Density	~1.12 ± .03 kg/l (+25°C)
pH-Value	5 – 7

## APPLICATION INFORMATION

### Recommended dosage

Field trials should be conducted to determine the optimum addition rates of Sika® Stabilizer-5014 TBM SA. As a guide to these trials, a dosage range of 3 – 5 % per m<sup>3</sup> of backfill grout is considered standard. Dosages outside this range can be used where improved workability, increased water reduction and/or further set retardation are required.

### Compatibility

Sika® Stabilizer-5014 TBM SA can be used with all types of Portland cements including sulphate resisting cement (Type V). For use with other special cements, please contact Sika Technical Department. Sika® Stabilizer-5014 TBM SA is compatible with accelerators such as Sika® Stabilizer-6001 SA. Sika® Stabilizer-5014 TBM SA should not be premixed with other admixtures. If other admixtures are to be used in annular grouts containing Sika® Stabilizer-5014 TBM SA, they must be dispensed separately. Contact Sika Technical Services for additional information.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### APPLICATION

Sika® Stabilizer-5014 TBM SA is added to the Component A mix. Never add Sika® Stabilizer-5014 TBM SA to the dry cement.

No extension to normal mixing time is necessary.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### Sika Gulf B.S.C. (c)

Tel: +973 177 38188

Email: info@bh.sika.com

Sika Kuwait Cons. Mat. & Paints Co WLL

Tel: +965 22 282 296

Email: sika.kuwait@kw.sika.com

Web: gcc.sika.com

#### Sika UAE LLC

Sika MB Construction Chemicals LLC

Sika International Chemicals LLC

Tel: +971 4 439 8200

Email: info@ae.sika.com

Web: gcc.sika.com

#### Sika Saudi Arabia Limited

Sika Construction Chemicals for

Manufacturing LLC

Riyadh / Jeddah / Dammam / Rabigh

Tel: +966 9200 22167

Email: info@sa.sika.com

Web: gcc.sika.com

#### Sika LLC - Oman

Sika MB LLC

Tel. +968 22 826 500

Email: info@om.sika.com

Web: gcc.sika.com



ISO 9001, 14001, 45001 – SGS:  
Sika MB LLC  
Sika International Chemicals LLC  
Sika Gulf B.S.C. (c)  
ISO 9001, 14001 – SGS:  
Sika Saudi Arabia Limited  
ISO 9001, 14001 – TÜV  
Sika MB Construction Chemicals LLC  
Sika Construction Chemicals  
for Manufacturing LLC  
ISO 9001 – LRQA  
Sika MB LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.



#### Product Data Sheet

Sika® Stabilizer-5014 TBM SA

August 2025, Version 01.01

021404071000245404

SikaStabilizer-5014TBMSA-en-AE-(08-2025)-1-1.pdf