

PRODUCT DATA SHEET

SikaFiber®-12-34

Special polypropylene fibre for concrete and gunite

DESCRIPTION

SikaFiber®-12-34 is a high quality, 100% virgin, mono-filament polypropylene fibre, coated with a surfactant to improve initial dispersion and bond with the cement paste, designed for the prevention of concrete spalling in the event of fire. It also reduces the occurrence of plastic shrinkage and plastic settlement cracking whilst enhancing the surface properties and durability of a cementitious matrix.

Suitable for use in hot and tropical climatic condition

USES

SikaFiber®-12-34 is used to prevent concrete spalling (breaking off of layers or pieces of concrete from the surface of a structural element when exposed to the high and rapidly increasing temperatures experienced in fires), mainly in underground structures. In the event of a fire, as the temperature of the concrete increases, the moisture in the concrete becomes steam. If this steam is unable to escape an increase in pressure inside the concrete builds up to the point where it exceeds the tensile capacity of the concrete causing pieces of concrete to be violently and explosively dislodged. The addition of suitable polypropylene fibres in cast concrete has been accepted to counteract explosive spalling. The fibres melt inside the concrete creating the necessary voids for the steam to escape thereby preventing spalling and so maintaining the integrity of the structural element.

- Concrete, mainly when HPC and low permeability concrete is specified because of the greater pore pressures that build up during heating
- Precast concrete tunnel segments
- Concrete submitted to very high temperatures

CHARACTERISTICS / ADVANTAGES

- Helps maintain the integrity of the whole structure in the event of fire
- Reduces future repair costs
- Provides passive fire protection to both shotcrete and cast concrete and an extremely cost effective solution when compared to alternatives such as sprayed coatings or barrier methods
- Beyond enhancing spalling resistance, addition of polypropylene fibres to wet shotcrete improves the ability to apply greater thicknesses in a single pass, reduces rebound, enhances early age crack control, reduces line pressure in spray pumps and may reduce the dosage of set accelerator

APPROVALS / CERTIFICATES

Complies with EN 14889-2: Polymer Fibres - Definitions, Specifications and Conformity; Class 1a

PRODUCT INFORMATION

Composition	Polypropylene	
Packaging	0.6 kg, 0.9 kg and 1 kg in water soluble bags and 450 kg jumbo bag	
Appearance / Colour	White fibre	
Shelf life	24 months from date of production if stored properly	
Storage conditions	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5 °C and +45 °C. Protect from direct sunlight, moisture and frost.	
Density	~0.91 kg/l (+25 °C)	
Dimensions	Length	~12 mm
	Diameter	~34 µm
Melting point	~160 °C	

TECHNICAL INFORMATION

Concreting guidance	The standard rules of good concreting practice for production and placing must be observed when using SikaFiber®-12-34 in concrete. Refer to relevant standards. Fresh concrete must be cured properly especially at high temperatures in order to prevent plastic and drying shrinkage. Use Sika® Antisol® products as a curing agent.
Resistance to alkalinity	Excellent

APPLICATION INFORMATION

Recommended dosage	SikaFiber®-12-34 is supplied ready to use. The accurate determination of the minimum fibre dosage to provide explosive spalling resistance can only be established by large scale fire testing of the concrete to be used on a specific project. Section 6.1 of the European Standard EN 1992 Eurocode 2 makes reference to the use of 2 kg/m ³ of polypropylene fibres to control explosive spalling in high strength concrete. This dosage provides a very good safety margin, but does not preclude the use of lower dosages if fire testing on large concrete samples has been carried out. Dosage rates of 1.5 kg/m ³ or less have been used after accurate trials. We recommend to perform trial mixes to establish the required performance. Please consult our Sika Technical Department for further assistance.
Compatibility	SikaFiber®-12-34 may be combined with all types of Portland cement, concretes containing pozzolanic materials such as; GGBS, PFA, micro-silica and the following Sika product ranges: <ul style="list-style-type: none">▪ Sika® ViscoCrete®▪ SikaPlast®▪ Sikament®▪ Plastiment®▪ Sika Aer® We recommend to perform trial mixes to establish the required performance when combining SikaFiber®-12-34 with the above or other admixtures. Please consult our Sika Technical Department.
Dispensing	Plant mixing: SikaFiber®-12-34 should be added to the mixer after all other ingredients and water. Use a mixing time that ensures uniform dispersion of the fibre. Truck mixing: SikaFiber®-12-34 is best added in the batching plant mixer; although in

cases where this may not be possible addition in the truck can be done. The fibre should be added first with ~30 % of the mixing water. Add the other ingredients, the remaining mixing water and continue mixing for a further few minutes at full speed to ensure uniform dispersion of the fibre.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA NORTHERN GULF

Bahrain / Qatar / Kuwait
Tel: +973 177 38188
sika.gulf@bh.sika.com
gcc.sika.com

SIKA SOUTHERN GULF

UAE / Oman / SIC
Tel: +971 4 439 8200
info@ae.sika.com
gcc.sika.com

SIKA SAUDI ARABIA

Riyadh / Jeddah / Dammam
Tel: +966 11 217 6532
info@sa.sika.com
gcc.sika.com



ISO 9001: Sika UAE LLC,
Sika Gulf B.S.C. (c),
Sika Saudi Arabia Co. Ltd,
Sika Qatar LLC
ISO 14001: Sika UAE LLC,
Sika Gulf B.S.C. (c),
Sika Saudi Arabia Co. Ltd
OHSAS: Sika UAE LLC,
Sika Gulf B.S.C. (c)

All products are supplied
under a management
system certified to conform
to the requirements of the
quality, environmental and
occupational health &
safety standards ISO 9001,
ISO 14001 and OHSAS
18001.

SikaFiber-12-34-en-AE-(08-2020)-1-2.pdf

Product Data Sheet

SikaFiber®-12-34

August 2020, Version 01.02
021408021010000102

