

PRODUCT DATA SHEET

Sikaplan®-700 Geotextile

Polypropylene protection fabric for drainage systems and underground waterproofing.

DESCRIPTION

Sikaplan®-700 Geotextile is a polypropylene non-woven fabric used as a filtration/separation layer in drainage systems. It is also used as a protection/ separation layer beneath sheet membrane waterproofing in underground or tunnel applications. Sikaplan®-700 Geotextile suitable for use in hot and tropical climatic conditions.

USES

The product is designed for:

- Filtration or separation in drainage systems
- As a protection layer beneath sheet waterproofing membranes in tunnels and other underground structures.

FEATURES

- Highly resistant to ageing.
- Optimized tensile strength and elongation.
- Resistant to all natural aggressive mediums found in ground water and soil.
- Suitable for in contact with soft water.
- Remain flexible in cold weather.
- Can be installed on damp substrates

PRODUCT INFORMATION

Packaging	Roll size: 2.10 m (roll width) × 70.00 m (roll length)	
Appearance and colour	Surface: structured Colour: white	
Shelf life	Unlimited, provided the storage conditions are met.	
Storage conditions	Rolls must be stored in the original package, in horizontal position in a cool and dry conditions. They must be protected from direct sunlight, rain, heat, snow and ice, etc.	
Thickness	~5.0 mm (±10%)	(EN ISO 9863-1)
Mass per area	~700 g/m² (±10%)	(EN ISO 9864)
TECHNICAL INFORMATION		
Resistance to static puncture	~5850 N	(EN ISO 12236)
Tensile strength	~35 kN/m	(EN ISO 10319)
Elongation at break	~50 %	(EN ISO 10319)

Product Data Sheet

Sikaplan®-700 GeotextileApril 2025, Version 01.01
020720701000242322

SYSTEM INFORMATION

Compatibility

Sikaplan®-700 Geotextile is suitable to be used in conjunction with the following product group;

- Sikaplan® WP membranes
- Sikaplan® WT membranes
- Sikaproof® A+ membranes
- Sikaproof® P1200 membranes
- Sikaplan® WP Protection sheet
- Sika® Waterbars

Please consult with Sika Technical Department for further assistance.

APPLICATION

Sikaplan®-700 Geotextile shall be installed on damp

Sikaplan®-700 Geotextile shall be installed by loose

However, the installation shall be carried out in con-

Note that as a result of specific local regulations the

may vary from country to country. Consult the local

Product Data Sheet for exact product data and uses.

The information, and, in particular, the recommenda-

tions relating to the application and end-use of Sika

products, are given in good faith based on Sika's cur-

properly stored, handled and applied under normal

conditions in accordance with Sika's recommenda-

tions. In practice, the differences in materials, sub-

strates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a

particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either

user of the product must test the product's suitability

products. The proprietary rights of third parties must

current terms of sale and delivery. Users must always

be observed. All orders are accepted subject to our

refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which

from this information, or from any written recommendations, or from any other advice offered. The

for the intended application and purpose. Sika re-

serves the right to change the properties of its

rent knowledge and experience of the products when

declared data and recommended uses for this product

junction with the approved waterproofing system.

substrates, however any water leakages shall be sealed with Sika® waterproof plugging mortar, or with

the help of proper de-watering sytem.

laid or mechanically fastening method.

LOCAL RESTRICTIONS

LEGAL NOTES

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

Sikaplan®-700 Geotextile is not resistant to permanent exposure to weathering and UV-light, therefore it must covered within 2 weeks after installation.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

In-situ concrete: Clean, sound and dry, homogeneous, free from oils and grease, dust and loose or friable particles.

Shotcrete: The profile of the shotcrete surface must not exceed a ratio of length to depth of 10:1 and the minimum radius must be 20 cm. The shotcrete surface must not contain broken or sharp aggregates.

Sika Gulf B.S.C. (c)

Tel: +973 177 38188 Email: info@bh.sika.com Sika Kuwait Cons. Mat. & Paints Co WLL Tel: +965 22 282 296 Email: sika.kuwait@kw.sika.com

Sika UAE LLC

Sika MB Construction Chemicals LLC Sika International Chemicals LLC Tel: +971 4 439 8200 Email: info@ae.sika.com

Web: gcc.sika.com

Sika Saudi Arabia Limited

Sika Construction Chemicals for Manufacturing LLC Riyadh / Jeddah / Dammam / Rabigh Tel: +966 9200 22167 Email: info@sa.sika.com Web: gcc.sika.com

will be supplied on request.

Sika LLC - Oman

Sika MB LLC Tel. +968 22 826 500 Email: info@om.sika.com Web: gcc.sika.com



Web: gcc.sika.com



Sikaplan-700Geotextile-en-AE-(04-2025)-1-1.pdf



Product Data Sheet Sikaplan®-700 Geotextile April 2025, Version 01.01 020720701000242322