

PRODUCT DATA SHEET

SikaSeal®-626 Fire Board+

Fire resistant coated protection board



DESCRIPTION

SikaSeal®-626 Fire Board+ is a mineral wool based protection board coated with the fire resistant, ablative coating Sikacryl®-625 Fire+. Can be combined with many other Sika passive fire protection products for sealing a wide range of service penetrations. Suitable for use in hot and tropical climatic conditions.

USES

- Restores the fire resistance performance of walls and floors which incorporate single and multiple service penetrations
- Can be combined with Sikacryl®-621 Fire+, Sikacryl®-625 Fire+, SikaSeal®-627 Fire Collar+ and SikaSeal®-629 Fire Wrap+

CHARACTERISTICS / ADVANTAGES

- Up to 4 hours fire resistance
- Easy to install, no need for specialist tools
- For face-fit (pattress-fit) and internal-fit installations
- Provides acoustic insulation
- Tested for a large variety of relevant wall and floor types

APPROVALS / CERTIFICATES

- CE Marking and Declaration of Performance to European Technical Assessment ETA-21/0887, based on EAD 350454-00-1104:2017 - Fire stopping and fire sealing products, penetration seals
- Fire Resistance EN 13501-2, UL-EU, Certificate No.UL-EU-01214-CPR

PRODUCT INFORMATION

Composition	Mineral wool based core, acrylic coating on one or two sides	
Packaging	Boards individually wrapped in a plastic foil. Refer to current price list for packaging variations.	
Shelf life	6 years from the date of production.	
Storage conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.	
Density	~160 kg/m ³	(Standard)
Dimensions	Coated board: length 1'200 mm, width 600 mm, thickness 30, 50 or 60 mm. Refer to current price list for packaging variations	

TECHNICAL INFORMATION

Resistance to fire	Refer to 'Approvals / Certificates' or contact Sika Technical Services for specific information.
Service temperature	-20 °C min. / +70 °C max.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

- Sika Application Manual: SikaSeal®-626 Fire Board+
- Brochure Sika Fire Protection Solutions

IMPORTANT CONSIDERATIONS

- Not suitable for load bearing applications.
- SikaSeal®-626 Fire Board+ may only be used for applications and in combination with products it was tested for.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The substrate must be clean, dry, sound, free from oils, grease, dust and loose or friable particles.

APPLICATION METHOD / TOOLS

Reference must be made to the relevant Sika Application Manual or contact Sika Technical Services for additional information.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA NORTHERN GULF

Bahrain / Kuwait
Tel: +973 177 38188
info@bh.sika.com
gcc.sika.com

SIKA SOUTHERN GULF

UAE / Oman / SIC
Tel: +971 4 439 8200
info@ae.sika.com
gcc.sika.com

Sika Saudi Arabia

Riyadh / Jeddah / Dammam
Tel. +966 11 217 6532
info@sa.sika.com
gcc.sika.com



ISO 9001: Sika UAE LLC,
Sika Gulf B.S.C. (C),
Sika Saudi Arabia Limited,
Sika International Chemicals LLC
ISO 14001: Sika UAE LLC,
Sika Gulf B.S.C. (C),
Sika Saudi Arabia Limited,
Sika International Chemicals LLC,
ISO 45001: Sika UAE LLC,
Sika Gulf B.S.C. (C),
Sika International Chemicals LLC.

All products are supplied under
a management system certified
to conform to the requirements
of the quality, environmental
and occupational health &
safety standards ISO 9001,
ISO 14001 and ISO 45001.

SikaSeal-626FireBoard+-en-AE-(03-2022)-1-1.pdf

Product Data Sheet
SikaSeal®-626 Fire Board+
March 2022, Version 01.01
020517100100000012

