

PRODUCT DATA SHEET

Sika® Stabilizer-2031 TBM

Excluder grease for TBM main bearing

DESCRIPTION

Sika® Stabilizer-2031 TBM is a grease based on synthetic oil used to protect the main bearing of TBM. The Product resists high water and ground pressures. It has very good lubricating and pumping properties, and adheres very well to all surfaces.

USES

Sika® Stabilizer-2031 TBM is used for:

- Effective protection of the main bearing gaskets. It prevents ingress of soil, water or dust into the main bearing sealing.

FEATURES

- Extrusion abilities designed to match TBM manufacturers' requirements
- Effective lubrication under heavy loads
- Proper adhesion to any metal
- Reduces dust formation
- Temperature stability providing pumping and lubricating properties, especially at very low or very high temperatures
- Particularly effective with low rpm

PRODUCT INFORMATION

Composition	Mixture of synthetic oil, additives and lubricants	
Packaging	Drum	230 kg for press plate pumps
Shelf life	12 months from date of production	
Storage conditions	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +50 °C. Always refer to the packaging. Refer to the current Safety Data Sheet for information on safe handling and storage.	
Appearance and colour	Homogeneous fibrous paste, black	
Density	(1.200 ± 0.050) kg/l	(ISO 758)
Flash point	> +190 °C	(ASTM D92)
Consistency	Tested at +25 °C	260 ± 10 (ASTM D217)

TECHNICAL INFORMATION

Specific advice	Pumpable properties	40–50 gr/min (after US steel Lt 37, at 10 bar and +25 °C)
	Biodegradability	> 60 % after 22 days
	Volatility	≤ 2 % (ASTM D972)
	Water washout	< 6 % (ASTM D1264)

SYSTEM INFORMATION

Compatibility Compatible with Sika® admixtures and other Sika® products. Contact Sika Technical Services for additional information.

APPLICATION INFORMATION

Consumption The consumption of the Product depends on the following parameters:

- TBM design such as sealing gap
- Operational parameters during tunneling such as cutterhead speed and TBM penetration rate

Contact Sika Technical Services for additional information.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Pump the Product by using the main bearing grease pumping system in TBM.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Gulf B.S.C. (c)
Tel: +973 177 38188
Email: info@bh.sika.com
Sika Kuwait Cons. Mat. & Paints Co WLL
Tel: +965 22 282 296
Email: sika.kuwait@kw.sika.com
Web: gcc.sika.com

Sika UAE LLC
Sika MB Construction Chemicals LLC
Sika International Chemicals LLC
Tel: +971 4 439 8200
Email: info@ae.sika.com
Web: gcc.sika.com

Sika Saudi Arabia Limited
Sika Construction Chemicals for Manufacturing LLC
Riyadh / Jeddah / Dammam / Rabigh
Tel: +966 12 692 7079
Email: info@sa.sika.com
Web: gcc.sika.com

Sika LLC - Oman
Master Builders Solutions LLC (part of Sika)
Tel. +968 22 826 500
Email: info@om.sika.com
Web: gcc.sika.com



ISO 9001, ISO 14001, ISO 45001 – SGS
- Sika UAE LLC
- Sika International Chemicals LLC
- Sika Gulf B.S.C. (c)
ISO 9001, ISO 14001 – SGS
- Sika Saudi Arabia Limited
ISO 9001, ISO 14001 – TÜV
- Sika MB Construction Chemicals LLC
- Sika Construction Chemicals for Manufacturing LLC
- Master Builders Solutions LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.



SikaStabilizer-2031TBM-en-AE-(07-2024)-2-1.pdf

Product Data Sheet
Sika® Stabilizer-2031 TBM
July 2024, Version 02.01
021404071000000142

