

PRODUCT DATA SHEET

SikaPaver[®] HC-120

HIGH PERFORMANCE COMPACTION AID FOR SEMI-DRY CONCRETE PRODUCTS

DESCRIPTION

SikaPaver[®] HC-120 is a high performance filling and compaction aid which has been designed to eliminate the stickiness of semi-dry concretes at elevated water-cement ratios. The resulting granular concrete leads to an even mold filling and less quality fluctuations while ensuring the targeted concrete compaction.

USES

- Concrete Pavers
- Masonry Blocks
- Roof Tiles
- Kerbstones
- Landscaping elements

FEATURES

SikaPaver[®] HC-120 has been designed especially for the application in semi-dry concrete and causes:

- Granular mold-filling properties despite elevated water contents
- Even concrete distribution into the individual chambers across the compaction mold
- Less quality variations and consequently less second grade products
- Better durability

SikaPaver[®] HC-120 improves the dispersion and wetting of cement, additives and pigments and hence allows reaching the target density in shorter time or the reduction of pore content at the same compaction effort.

PRODUCT INFORMATION

Composition	Blend of surfactants
Packaging	200 L Drum and 1000 L flowbin
Shelf life	12 months from date of production if stored properly in original, unopened packaging.
Storage conditions	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5 °C and +45 °C. Protect from direct sunlight and frost.
Appearance and colour	Orange Liquid Note: Upon prolonged storage or exposure to direct sunlight colour may fade, however the product properties remain unchanged
Density	~1.00 kg/l (+25 °C)

APPLICATION INFORMATION

Recommended dosage	0.2 - 0.5% of cement weight
Dispensing	SikaPaver [®] HC-120 shall be introduced at the end of the mixing process to ensure its uniform distribution. The necessary mixing time after the admixture dosage depends on the individual mixer.

Compatibility

Before use suitability tests must be performed.

Sufficient compaction of base and face concrete while in parallel avoiding capillary porosity is essential to ensure the targeted performance parameters of the manufactured semi-dry concrete elements. For further information and advice, please contact our Technical Service Department. The use of SikaPaver® HC-120 in wet cast concrete is not suitable.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Gulf B.S.C. (c)

Tel: +973 177 38188

Email: info@bh.sika.com

Sika Kuwait Cons. Mat. & Paints Co WLL

Tel: +965 22 282 296

Email: sika.kuwait@kw.sika.com

Web: gcc.sika.com

Sika UAE LLC

Sika MB Construction Chemicals LLC

Sika International Chemicals LLC

Tel: +971 4 439 8200

Email: info@ae.sika.com

Web: gcc.sika.com

Sika Saudi Arabia Limited

Sika Construction Chemicals for Manufacturing LLC

Riyadh / Jeddah / Dammam / Rabigh

Tel: +966 12 692 7079

Email: info@sa.sika.com

Web: gcc.sika.com

Sika LLC - Oman

Master Builders Solutions LLC (part of Sika)

Tel: +968 22 826 500

Email: info@om.sika.com

Web: gcc.sika.com



ISO 9001, 14001, 45001 – SGS
- Sika UAE LLC
- Sika International Chemicals LLC
- Sika Gulf B.S.C. (c)
ISO 9001, 14001 – SGS
- Sika Saudi Arabia Limited
ISO 9001 – TÜV
- Sika MB Construction Chemicals LLC
- Sika Construction Chemicals for Manufacturing LLC
- Master Builders Solutions LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.



Product Data Sheet

SikaPaver® HC-120

July 2024, Version 02.01

02140406100000059