BUILDING TRUST

PRODUCT DATA SHEET

Wabo®Flex 5403

Aluminum Floor Profile with TPE insert

DESCRIPTION

Wabo®Flex 5403 is an aluminum floor expansion-joint profile incorporating a flexible, replaceable thermoplastic elastomer (TPE) insert.

USES

Wabo®Flex 5403 is designed for floor expansion joints requiring multidirectional movement accommodation. The system is suitable for areas subjected to pedestrian and light-vehicle traffic.

FEATURES

- Mill finish aluminum profile comes as perforated or smooth
- Easy onsite installation
- Multi directional movement

PRODUCT INFORMATION

Composition	Aluminum (6063-T5) Thermoplastic Elastomer (TPE)
Packaging	Supplied in standard 3-meter profile lengths
Colour	Black, gray and cream
Appearance and colour	

Shelf life

Thermoplastic elastomer (TPE): 24 months if stored in a cool, dry environ ment, protected from direct sunlight, UV radiation, ozone, and excessive humidity.
Aluminum Alloy (6063-T5): Indefinite provided the material remains free from excessive corrosion, mechanical damage, or other deterioration that could affect its intended performance.

Storage conditions

The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +15 °C and +25 °C


Density

Thermoplastic elastomer (TPE):	~1.21 g/cm³
Aluminum Alloy (6063-T5):	~2.7 kg/cm³


Dimensions

Profile Code	5403-030	5403-030C
Joint Width (a)	30 mm	30 mm
Top Surface Width (b)	32 mm	32 mm
Installation Depth (h)	50 mm	50 mm
Block Out Width (s)	124 mm	90 mm

– Wabo®Flex 5403-030



– Wabo®Flex 5403-030C



TECHNICAL INFORMATION

Shore A hardness	Thermoplastic elastomer (TPE)	~65 (ISO 868)
Modulus of elasticity in compression	Aluminum aloy (6063.T5)	~69.5 GPa
Tensile strain at break	Thermoplastic elastomer (TPE)	~4.2 MPa (ISO 37, DIN 53504)
Movement capability	± 10 mm	
Coefficient of thermal expansion	Aluminum aloy (6063-T5)	~23.5 x 10^{-6} / K
Chemical resistance	Alcohol	Excellent
	Sulphuric Acid	Good
	Detergent	Good
	Thermoplastic elastomer (TPE)	
Temperature resistance	Max. Dynamic Service Temperature	90 °C
	Max. Static Service Temperature	135 °C
Thermal conductivity	Aluminum aloy (6063-T5)	~200 W/(m·K)
Electrical resistivity	Aluminum aloy (6063-T5)	~0.035 x 10^{-6} Ω·m
Tensile stress at specified elongation	Thermoplastic elastomer (TPE) at 100 %	~1.85 MPa (ISO 37, DIN 53504)
	Thermoplastic elastomer (TPE) at 300 %	~2.5 MPa (ISO 37, DIN 53504)
Water resistance	Thermoplastic elastomer (TPE)	Excellent
Elongation at break	Thermoplastic elastomer (TPE)	~600 % (ISO 37, DIN 53504)
Resistance to ozone	Thermoplastic elastomer (TPE)	Excellent

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTATION

- General Method Statement (GMS)
- Substrate preparation for Wabo floor joints

IMPORTANT CONSIDERATIONS

- Do not install if the joint's anticipated movement will exceed the system's movement range.
- Deliver product in each manufacturer's original, intact, labeled packaging. Protect the work area with appropriate plastic sheeting.
- Store all components in a clean, dry and off the ground location to protect from weather and construction activities.
- For installation 4*50 mm screw and 6 mm PVC plugs are necessary.
- Inspection, of the instalation, should be done periodicaly.
- For advice and instructions please contact local Sika representative.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Gulf B.S.C. (c)
Tel: +973 177 38188
Email: info@bh.sika.com
Sika Kuwait Cons. Mat. & Paints Co WLL
Tel: +965 22 282 296
Email: sika.kuwait@kw.sika.com
Web: gcc.sika.com

Sika UAE LLC
Sika UAE LLC (Branch)
Sika International Chemicals LLC
Tel: +971 4 439 8200
Email: info@ae.sika.com
Web: gcc.sika.com

Sika Saudi Arabia Limited
Riyadh / Jeddah / Dammam / Rabigh
Tel: +966 9200 22167
Email: info@sa.sika.com
Web: gcc.sika.com

Sika MB LLC
Oman
Tel. +968 22 826 500
Email: info@om.sika.com
Web: gcc.sika.com

ISO 9001, 14001, 45001 – SGS:
- Sika UAE LLC
- Sika International Chemicals LLC
- Sika Gulf B.S.C. ©
ISO 9001, 14001 – SGS:
- Sika Saudi Arabia Limited
ISO 9001, 14001 – TÜV:
- Sika UAE LLC (Branch)
ISO 9001 – URS:
- Sika MB LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.