BUILDING TRUST

PRODUCT DATA SHEET

Wabo® W Wall Guard

Rubber Wall Guards

DESCRIPTION

Wabo® W Wall Guard is a heavy duty protection for walls and columns.


USES

Protects walls from damage caused by vehicles or carts.

FEATURES

- High impact resistance moulded rubber
- Excellent weather resistance
- Stain proof
- Easy installation
- Eco-Friendly


PRODUCT INFORMATION

Composition	Natural Rubber/ Styrene-Butadiene Rubber (NR/SBR) Ethylene Propylene Diene Monomer (EPDM)
Packaging	Supplied in standard 3-meter length. Custom lengths are available upon request.
Appearance and colour	 Available with or without yellow strip
Shelf life	**Natural Rubber/ Styrene-Butadiene Rubber (NR/SBR):** 5 years if stored in a cool, dry environment, protected from direct sunlight, UV radiation, ozone, and excessive humidity. **EPDM (Ethylene Propylene Diene Monomer):** 5 years if stored in a cool, dry environment, protected from direct sunlight, UV radiation, ozone, and excessive humidity.
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C.

Dimensions

Width (mm)	Thickness (mm)
200	25
200	30
120	30
200	40
200	50

Cross section



TECHNICAL INFORMATION

Shore A hardness	NR/SBR	~75	(ASTM D2240)
	EPDM	~70	
Tensile strength	NR/SBR	12 N/mm²	(ASTM D412)
	EPDM	10 N/mm²	
Resistance to tear	NR/SBR	≥30 kN /m	(ASTM D624)
	EPDM	≥30 kN /m	
Retention of properties after heat ageing	NR/SBR		
	Shore A Hardness	+5	(ASTM D573)
	Tensile Strength	-25%	
	Elongation at Break	-22%	
	EPDM		
	Shore A Hardness	+10	(ASTM D573)
	Tensile Strength	-25%	
	Elongation at Break	-35%	
Water resistance	NR/SBR	Good	
	EPDM	Excellent	
Flexibility at low temperature	NR/SBR	Good	(ASTM D746)
	EPDM	Good	
Elongation at break	NR/SBR	≥325 %	(ASTM D412)
	EPDM	≥200 %	

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTATION

General Method Statement (GMS)

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Wabo® W Wall Guard can be fixed horizontally to a wall or placed in short vertical strip on flat or curved surfaces using fix bolt.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Gulf B.S.C. (c)
Tel: +973 177 38188
Email: info@bh.sika.com
Sika Kuwait Cons. Mat. & Paints Co WLL
Tel: +965 22 282 296
Email: sika.kuwait@kw.sika.com
Web: gcc.sika.com

Sika UAE LLC
Sika UAE LLC (Branch)
Sika International Chemicals LLC
Tel: +971 4 439 8200
Email: info@ae.sika.com
Web: gcc.sika.com

Sika Saudi Arabia Limited
Riyadh / Jeddah / Dammam / Rabigh
Tel: +966 9200 22167
Email: info@sa.sika.com
Web: gcc.sika.com

Sika MB LLC
Oman
Tel. +968 22 826 500
Email: info@om.sika.com
Web: gcc.sika.com

ISO 9001, 14001, 45001 – SGS:
- Sika UAE LLC
- Sika International Chemicals LLC
- Sika Gulf B.S.C. ©
ISO 9001, 14001 – SGS:
- Sika Saudi Arabia Limited
ISO 9001, 14001 – TÜV:
- Sika UAE LLC (Branch)
ISO 9001 – URS:
- Sika MB LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.